

Name of Work: Restoration of Road from Plot No. G51G to G86G & PP 11 to DP 13 at TANSIDCO Industrial Estate, Kakkalur in Thiruvallur District

EMD - Rs.51,000/-

Date of Tender : 13.04.2022

SCHEDULE OF QUANTITIES

SL. NO	QTY	DESCRIPTION OF WORK	TNBP NO	RATE IN FIGURES AND WORDS	UNIT	AMOUNT
1	3442 Sqm (Three Thousand Four Hundred and Forty Two)	Picking 2cm to 10cm thick old metalled surface and sectioning as directed by TANSIDCO Engineers etc., complete.	85		1 Sqm (One Square Metre)	
2	264 Cum (Two Hundred and Sixty Four)	Providing Well Gravel Soling for base & berms of specified thickness including cost and conveyance of well gravel to site and stacking them to departmental gauge for pre-measurment including labour charges for spreading and watering with all leads for good water, consolidation by power roller rolling and other charges for the tools and plants engaged etc., complete complying with standard specification. (Payment will be made for consolidated thickness of well gravel only).	MORTH 111, 112, 401 & 900		1 Cum (One Cubic Metre)	

NO.OF CORRECTIONS IN FIGURE:

NO.OF CORRECTIONS IN WORDS:

CONTRACTOR

SUPERINTENDING ENGINEER i/c

SL. NO	QTY	DESCRIPTION OF WORK	TNBP NO	RATE IN FIGURES AND WORDS	UNIT	AMOUNT
3	633 Cum (Six Hundred and Thirty Three)	Providing and laying WET MIX MACADAM Base Course of 250mm compacted thickness in two layers of 125 mm thick or else as specified on prepared sub base with graded stone aggregate using 0.396cum of 45.00-22.40mm graded metal, 0.528cum of 22.40-2.36mm graded metel and 0.396cum of 2.36mm graded metal and below including premixing the material with water at OMC in mechanical mix plant carriage of mixed materials by tipper trucks to paver site, laying in uniform layers with paver, spreading the mix for uniform thickness with mechanical paver to the specified grades and cross sections and compaction by 80 -100 KN vibratory roller to required density etc. including labour for attending the paver site, including hire charges and fuel charges for tipper trucks, paver finisher, vibratory rollers and all other tools and plants required and all other incidental charges etc., complete as per Clause 406 of MORTH and as directed by Engineer.	MORTH 111, 112, 406 & 900		1 Cum (One Cubic Metre)	
4	113 Cum (One Hundred and Thirteen)	Plain Cement Concrete 1:5:10 (One cement, five of M Sand and ten of Hard Broken Stone Jelly) using 40mm gauge hard broken stone jelly for foundation inclusive of dewatering if found necessary, shoring, strutting, side shuttering, ramming, curing and laid in layers not more than 15cm thick etc., complete complying with standard specification.	28		1 Cum (One Cubic Metre)	
5	169 Cum (One Hundred and Sixty Nine)	Reinforced Cement Concrete of M30 Grade Design Mix using M Sand , 10mm and 20mm gauge HB stone jelly for all RCC items of works excluding centering, shuttering & also cost of reinforcement grill in position but including the cost of mixing concrete, placing, vibrating with mechanical vibrator, finishing and curing etc. complete and as directed by the SIDCO Engineers.	30		1 Cum (One Cubic Metre)	

CONTRACTOR

NO.OF CORRECTIONS IN FIGURE:

NO.OF CORRECTIONS IN WORDS:

SUPERINTENDING ENGINEER i/c

SL. NO	QTY	DESCRIPTION OF WORK	TNBP NO	RATE IN FIGURES AND WORDS	UNIT	AMOUNT
6	11 MT (Eleven)	Supplying, fabricating and placing Reinforcement Steel of high yield strength ribbed bar of various diameter and grade conforming to IS1786 of reinforced concrete work. The work including decoiling, straightening, cutting, bending, fabricating and placing in position at all levels and floors including lead and lift according to drawings, specifications, etc complete. Supply and use of 18Gauge black annealed binding wire double fold to tie the bars in position, chairs pins, space bars, unauthorised laps which will not be measured separately neither for payment nor for reconsilation and providing precast cement / pvc cover blocks for main reinforcement to ensure specified cover and as directed. Steel and binding wire will be procured by the contractor at his own cost.	30 & 86		1 MT (One Metric Tonne)	
7	90 Sqm (Ninety)	Supplying and erecting Shuttering with necessary supports for Plane Surfaces such as RCC Column boxing, top & bottom slabs, sill slabs, sunshade with all cross bracings including strutting using silver oak (country wood) joists of size 10cm x 6.5cm spaced at about 90cm centre to centre etc., complete.	86 & 86A		1 Sqm (One Square Metre)	
8	488 RM (Four Hundred and Eighty Eight)	Providing Groove Cutting of 5mm width and 60mm average depth in the existing Reinforced Cement Concrete including hire charges for cutting machine, cost of cutting wheel, watering charges for cleaning, cost of bitumen and filling charges and all labour charges etc. complete.	Special		1 RM (One Running Metre)	
9	1125 Sqm (One Thousand One Hundred and Twenty Five)	Levelling and Compacting the Reinforced Cement Concrete of M30 Grade Design Mix including vacuum dewatering finishing the surface with mechanical traveller finishing, fixing and removing the inner channel after finishing the works with proper gradient and alignment including all materials and labours and tools and plant etc., complete and as directed by the SIDCO Engineers.	30		1 Sqm (One Square Meter)	

CONTRACTOR

NO.OF CORRECTIONS IN FIGURE:

NO.OF CORRECTIONS IN WORDS:

SUPERINTENDING ENGINEER i/c

SL. NO	QTY	DESCRIPTION OF WORK	TNBP NO	RATE IN FIGURES AND WORDS	UNIT	AMOUNT
10	2025 Sqm (Two Thousand and Twenty Five)	Providing and laying Prime Coat over WMM surface using 6kgs of bitumen Emulsion for 10 Sqm area including cost and conveyance of bituminous binder including labour charges for preparing the surface and applying the required quantity of bitumen as prime coat by bitumen sprayer etc., complete as per clause 502 of MORTH specification.	MORTH 502		1 Sqm (One Square Metre)	
11	2025 Sqm (Two Thousand and Twenty Five)	Providing and laying Tack Coat over WMM surface treated with priming coat using 2.50kgs of bitumen Emulsion for 10 Sqm area including cost and conveyance of bituminous binder including labour charges for preparing the surface and applying the required quantity of bitumen as tack coat by bitumen sprayer etc., complete as per clause 503 of MORTH specification.	MORTH 503		1 Sqm (One Square Metre)	
12	3260 Sqm (Three Thousand Two Hundred and Sixty)	Providing and laying Tack Coat over existing BT surface treated with priming coat using 3.00kgs of bitumen Emulsion for 10 Sqm area including cost and conveyance of bituminous binder including labour charges for preparing the surface and applying the required quantity of bitumen as tack coat by bitumen sprayer etc., complete as per clause 503 of MORTH specification.	MORTH 503		1 Sqm (One Square Metre)	

CONTRACTOR

NO.OF CORRECTIONS IN FIGURE:
NO.OF CORRECTIONS IN WORDS:

SUPERINTENDING ENGINEER i/c

SL. NO	QTY	DESCRIPTION OF WORK	TNBP NO	RATE IN FIGURES AND WORDS	UNIT	AMOUNT
13	116.50 Cum (One Hundred and Sixteen Point Five Zero)	Providing and laying 50mm compacted thick Bituminous Macadam using 0.42cum of 26.50 - 11.20 mm graded metal and 0.10cum of 11.20 - 2.80mm graded metal and 0.18cum of 2.80mm and below with 38 Kgs of bitumen for premixing 10Sqm including cost and conveyance of all materials to CMP site, heating the bitumen and aggregates to required temperature and mixing them in required temperature in central Hot mix plant 20-30 tons capacity conveying the mix by Tipper trucks to paver site, spreading the mix in required temperature for uniform thickness of 50mm with mechanical paver to the specified grades and cross sections and compaction by 8-10 T power roller to required density etc. including labour for loading bitumen into bitumen tank and metal to feeder unit, labour for attending the paver site etc. including hire charges and fuel charges for 20-30T CMP with bitumen boiler, tipper trucks, paver finisher, power rollers and all other tools and plants employed etc., complete as per clause 504 of MORTH Specification.	MORTH 501 & 504		1 Cum (One Cubic Metre)	

CONTRACTOR

NO.OF CORRECTIONS IN FIGURE:

NO.OF CORRECTIONS IN WORDS:

SUPERINTENDING ENGINEER i/c

SL. NO	QTY	DESCRIPTION OF WORK	TNBP NO	RATE IN FIGURES AND WORDS	UNIT	AMOUNT
14	200 Cum (Two Hundred)	Providing and laying 40mm compacted thick Semi-Dense Bituminous Concrete using 0.10cum of 13.20mm Graded IRC HBG metal, 0.16cum of 11.20mm graded IRC HBG metal, 0.16cum of 6.70mm graded IRC HBG metal and 0.18cum of 2.80mm and below with 38 Kgs of bitumen for premixing per 10Sqm including cost and conveyance of all materials to CMP site, heating the bitumen and aggregates to required temperature and mixing them in required temperature in central Hot mix plant 20-30 tons capacity conveying the mix by Tipper trucks to paver site, spreading the mix in required temperature for uniform thickness of 40mm with mechanical paver to the specified grades and cross sections and compaction by 8-10 T power roller to required density etc. including labour for loading bitumen into bitumen tank and metal to feeder unit, labour for attending the paver site etc. including hire charges and fuel charges for 20-30T CMP with bitumen boiler, tipper trucks, paver finisher, power rollers and all other tools and plants required including all other incidental charges etc., complete as per clause 508 of MORTH using CMP.	MORTH 501 & 511		1 Cum (One Cubic Metre)	
14 Items (Fourteen Items Only)					Total in Rs.	
Note: The tender invited excluding GST. At the time of acceptance of the tender and signing of agreement, the applicable GST of 18% will be included for this work.						

CONTRACTOR

NO.OF CORRECTIONS IN FIGURE:
NO.OF CORRECTIONS IN WORDS:

SUPERINTENDING ENGINEER i/c