

PERIYAKODIVERY TOWN PANCHAYAT SCHEDULE - A

Est. No.:
Estimate Amount: Rs. 20.00 Lakh
EMD.Amount (1%):
Tender Date & Time:

Sold to : Thiru.
Challan No.
Date:

Schedule of rates and approximate quantities to accompany the tender for the work of

Name of work: Construction of Storm Water Drain at Ward no.11, Sathy - K.N.Palayam main road, West side in Periyakodivery Town Panchayat, Erode District.

- The quantities have given are those upon which the lump-sum tender cost at the work is caused but they are subject to alterations, omissions, deductions or additions as provided for in the conditions of the contract and do not necessarily show the actual quantities of the work to be done.
- a) The unit of rates noted below are those governing payment for extras or deductions for omission according to the conditions of the contract as set forth in the conditions and specification for the contract.
- It is to be expressively understood that the measured work it is to be taken out (Not withstanding any customarily practice to the contrary according to the actual quantities when the place and finished accordingly to the Drawings or as may be ordered time to time by the Town Panchayat Engineer and the cost calculated by works connected there with. The rate quoted is for the works in site and complete in every respect.
- b)
- c) The material required for the works must be supplied by the contractor and of the approved quality

PERIYAKODIVERY TOWN PANCHAYAT**TENDER SCHEDULE**

Name of work: Construction of Storm Water Drain at Ward no.11, Sathy - K.N.Palayam main road, West side in Periyakodivery Town Panchayat, Erode District.

Scheme : NNT 2021-2022

Estimate Amount : Rs.1.25 Lakh

Sl. No	Quantity	Description of work	TNDSS & Specification No.	Rate in		UNIT	AMOUNT
				Figures	Words		
1	2	3	4	5	6	7	8
1	35.00 M3	Earth Work Excavation for foundation in all types of soils and sub soils to full depth (such as Soils in Rock / Silt / Light Black Cotton Soil / Ordinary Soil) except in rock requiring blasting but inclusive of shoring, shuttering and bailing out water wherever necessary and refilling the sides of foundation with excavated earth other than sand in layers of 150 mm thick well rammed and consolidated, depositing the surplus earth in places shown by the Departmental Officers with initial lead of 10 m and initial lift of 2 m. Complete as per TNSS 23 & 24, V, VI (S2), VII, 9,10	TNSS 23 & 24, V, VI (S2), VII, 9,10			1M3 (One cubic metre)	
2	5.00 M3	Plain Cement Concrete of mix 1 : 4 : 8 (One part Cement, four part sand & eight part of aggregates) using 40mm gauge hard broken metal from approved quarry including all cost, conveyance of materials to site with proper mixing, compacting, finishing and curing etc., complete as per standard specification. TNDSS NO: 28 V, VI (S2) V,VI (S5A) VII	TNDSS NO: 28 V, VI (S2) V,VI (S5A) VII			1M3 (One cubic metre)	

Bidder's Signature

Sl. No	Quantity	Description of work	TNDSS & Specification No.	Rate in		UNIT	AMOUNT
				Figures	Words		
1	2	3	4	5	6	7	8
3	78.00 M2	Supplying and erecting centering for Sides and Soffits including necessary supports and strutting upto 3.29m height for plane surfaces as detailed below in all floors with all cross bracings using mild steel sheets of size 90mm x 60mm and 10BG stiffened with welded mild steel angles of size 25mm x 25mm x 3mm for boarding, laid over silver oak joists of size 10cm x 6.5cm spaced at about 90cm centre to centre and supported by casurina props of 10cm to 13cm dia supported at not more than 75cm centre to centre etc complete Complying with standard Specification without Strutting. TNDSS NO or NBC No 30(S) 86 86 A V, VI(S3)VII	TNDSS NO or NBC No 30(S) 86 86 A V, VI(S3)VII			1M2 (One square metre)	
4	10.00 M3	Plain Cement Concrete 1:3:6 (one cement, three M-sand, six aggregate) using 20mm size ISS HBG metal machine crushed from approved quarry including cost and conveyance of all materials to site, loading and unloading charges and labour charges for mixing, laying and curing but excluding cost of reinforcement etc. Complete with std. Specifications. TNDSS NO: 24	TNDSS NO: 28 & VI (S2) VI (S5A) VII			1M3 (One cubic metre)	
5	20.00 M2	Providing Granolithic floor finish of the 25mm thickness with plain cement concrete 1:2:4 (One Cement, Two M-sand and Four aggregate) using 10 to 12mm gauge hard broken stone jelly including laying, finishing and the top rubbed smooth with power trawl, thread lining, curing etc. complete complying with standard specification and as directed by the departmental officers.	Special			1M2 (One square metre)	