Item Rate BoQ

Tender Inviting Authority: Commissioner, Thoothukudi City Municipal Corporation

Name of Work :Design, Fabrication, Erection and delivery of 7 Cu.M Capacity Tipper Lorry On your Supplied Chassis of Thoothukudi Corporation (2Nos).

Contract No: 32/22-23/AEE(ES)

Name of the Bidder/								
Bidding Firm								
/ Company :								
PRICE SCHEDULE (This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevent columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only)								
NUMBER #	TEXT #	NUMBE	TEXT #	NUMBER	NUMBER #	NUMBER #	TEXT <mark>#</mark>	
SI.	Item Description	Quantity	Units	Estimated	BASIC RATE In	TOTAL AMOUNT	TOTAL AMOUNT	
No.				Rate in	Figures To be	in	In Words	
				Rs. P	entered by the	Rs. P		
					Bidder			
					Rs. P			
1	2	3	4	5	6	7	8	

1 Design, Fabrication, Erection and deivery of 7Cum Garbage Tipper on New Chassis Vehicle with wheel base 3000mm Chassis BS-VI with PTO prov. CARGO TIPPER Chassis for Thoothukudi Corporation Solid Waste Management Activities. Chassis Specification would be : Overall Length X Breadth X Height in mm Overall Size: 3444 mm x 2150 mm x 865 mm, Overall, Height of the Tipper from Ground Level is 2700mm. Overall Volumetric Capacity is 7. OCu.m Capacity Tipping Angle: 48 Degree Hydraulically Operating System with driven power from Plain Eng ine. Hydraulic systems: Wipro, IPH, or Equivalent Reputed Make Hydraulic pressure control valve, Hydraulic Tank, PTO with Proper Connectors, ISI Standard Hydraulic hoses, Hydraulic pressure control valve, Hydraulic Tank, PTO with Pump, non-return Adopters. Over all body Should be made mild steel 3 MM Thickness Sheet and Bottom Frame is Structured by 100 x 50 x 6mm thickness "U" Channel with Proper Kilt and fasteners, and Bottom Platform Structure formed with 50 x 50 x 6mm L angle and all the corner post covered with channel and front edge bottom and side of the tipper fitted with machine fold 3mm M.S sheet with neet x- ray welding side kilt and bottom Tipping plates place with 25mm plates. And rear most jack post fitted with 35 mm M.S tension rod for tipping purpose. Paintings: one coat of Epoxy primer and Painting with two coats of anticorrosive paint as per the specified color and printing the lettering as per the direction of the departmental officers and as per standard specifications.The detailed specifications for the tank built is given in separate sheet.	2.00 1Nos(One Number)	0.00 INR Zero Only			
Total in Figures		0.00 INR Zero Only			
Quoted Rate in Words	INR Zero Only				