

THIRUPARAPPU TOWN PANCHAYAT
TENDER SCHEDULE

Name of work: Construction of Modern Gasifier Crematorium at Thirunanthikarai in Thiruparappu Town Panchayat

Estimate Amount: 146.00 Lakhs
EMD. Amount: 14600000

Tender Date
Issued to

BILL OF QUANTITIES

Sl No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
1	294.13	M3	Earth work excavation for foundation in Hard stiff clay, stiff black cotton, hard red earth, shales murrum, gravel, stoney earth and earth mixed with small size boulders SS 20B and Sand, silt or other loose soil, wet sand, silt not under water, light black cotton soil, sandy loam ordinary soil and to full depth as may be directed except in hardrock requiring blasting inclusive of shoring shuttering and baling out water wherever necessary refilling the sides of foundation with excavated soil other than sand in layers of 15cm thick well rammed and completed, cleaning and levelling the site etc., complete - Footings - First Depth Unto 2.00M			cum	
2	7.90	M3	Earth work excavation for foundation in Hard stiff clay, stiff black cotton, hard red earth, shales murrum, gravel, stoney earth and earth mixed with small size boulders SS 20B and Sand, silt or other loose soil, wet sand, silt not under water, light black cotton soil, sandy loam			cum	
3	12.68	M3	Earth work excavation for foundation in Hard stiff clay, stiff black cotton, hard red earth, shales murrum, gravel, stoney earth and earth mixed with small size boulders SS 20B and Sand, silt or other loose soil, wet sand, silt not under water, light black cotton soil, sandy loam ordinary soil and to full depth as may be directed except in hardrock requiring blasting inclusive of shoring shuttering and baling out water wherever necessary refilling the sides of foundation with excavated soil other than sand in layers of 15cm thick well rammed and completed, cleaning and levelling the site etc., complete - Plinth Beam			cum	

Sl No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
4	14.25	M3	Earth work excavation for foundation in Hard stiff clay, stiff black cotton, hard red earth, shales murram, gravel, stoney earth and earth mixed with small size boulders SS 20B and Sand, silt or other loose soil, wet sand, silt not under water, light black cotton soil, sandy loam ordinary soil and to full depth as may be directed except in hardrock requiring blasting inclusive of shoring shuttering and baling out water wherever necessary refilling the sides of foundation with excavated soil other than sand in layers of 15cm thick well rammed and completed, cleaning and levelling the site etc., complete - Plinth Beam			cum	
5	2.00	Cum	Earth work excavation in all soils and sub soils to full depth as may be directed by the departmental officers except in hard rock requiring blasting but inclusive of shoring, strutting and baling out water wherever nessasary and depositing the earth within initial lead of 10 metre and initial lift of 2 metre etc., complete as per Standard specifications			Cum	
6	18.39	M3	Supplying and filling in foundation and basement with filling Msand in layers of not more than 15cm.thick well rammed watered and compacted etc., complete complying with standard specification.			cum	
7	183.38	M3	Supplying and filling of well gravel by lorry in basement filling including conveyance loading and unloading charges and all other incidental charges filling laying watering and consolidation etc., complete as directed by the Dept., Officers with standard specification.			cum	
8	69.96	M3	Plain Cement concrete 1:4:8 (one cement, four sand, eight aggregate) using 40mm gauge hand broken granite stone jelly for foundation including dewatering if found necessary and laid in layers of not more than 15 cm thick and compacted,etc., complete complying with standard specification.			cum	

Sl No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
9			Supplying and erecting steel centering including necessary supports for plane surfaces for Reinforced Cement Concrete works such as column footings, column pedestals, plinth beams, grade beams, staircase steps, etc. which require only nominal strutting using mild steel sheets of size 90cm x 60cm and 10 BG stiffened with welded mild steel angles of size 25mm x 25mm x 3 mm for boarding, laid over silver oak joists of size 10cm x 6.5cm spaced at about 75cm centre to centre or at suitable intervals etc. complete in all floors complying with standard specification				
0	427.36	M2	0.00			sqm	
0	189.54	M2	0.00			sqm	
0	605.01	M2	0.00			sqm	
10			Providing and laying in position Standardised Concrete Mix M-20 Grade in accordance with IS 456 - 2000 using 20mm and down graded hard broken granite stone jelly for all RCC items of works with minimum cement content of 325Kg/ cum and maximum water cement ratio of 0.55 including admixture (Plasticiser / super plasticiser) in recommended proportions as per IS 9103 to accelerate, related setting of concrete, improve workability without impairing strength and durability with about (5.0cum), 7730Kg of 20mm machine crushed stone jelly and with about (3.3 cum), 5156kg of 10 - 12mm machine crushed stone jelly and with about (4.79cum) 7670 kg of sand, but excluding cost of reinforcement grill and fabricating charges centering and shuttering but including laying, vibrating with mechanical vibrators, finishing, curing, etc and providing fixtures like fan clamps in the RCC floor / roof slabs wherever necessary without claiming extra cost etc., complete complying with standard specification and as directed by the departmental officers - The Coarse and Fine aggregates to be used should comply with the requirements of IS standards. (No separate payment will be made by the Department for the excess usage of materials) - Upto Basement				
0	49.54	M3	Upto Basement			cum	
0	13.10	M3	Ground Floor			cum	

Sl No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
0	4.61	M3	First Floor			cum	
0	75.08	M3	Second Floor			cum	
11	5.47	Mt	Supply and fabrication of steel required for all RCC items of works involved in the schedule, cost of steel at site fabrication, labour charges for cleaning the rods straightening, cutting, bending, tying grills, including overlapping to the required length whenever necessary and placing the reinforcement in position as as per design given and specified in the drawings, including cost of binding wire, provision of spacer bars, cover blocks and all other incidental charges etc complete as per standard specification			MT	
12	35.00	Mt	Damp proof course with Cement Mortar 1:4 (One Cement and Four sand) 20mm thick mixed with best approved quality water proofing compound conforming to Indian Standard specification as specified by the departmental officers at 2% by weight of cement used and finishing, curing etc. complete complying with standard specification.			MT	
13	0.00	0.00	Brick work in CM 1:5 (one cement & Five sand) using II class ground moulded bricks of size 9"X43/8"X 23/4" standard specification including finishing, curing, etc., complete complying with standard specification (Masonry projections wherever necessary for obtaining required elevation shall be done without extra cost) - Ground Floor			0	
0	83.28	M3	Upto Basement			cum	
0	84.36	M2	Ground Floor			sqm	
0	13.00	M3	First Floor			cum	
14	107.84	M2	Brick Partition walls in CM 1:3 (one cement & three sand) using II class ground moulded bricks of size 9"X43/8"X23/4" using hoop iron reinforcement 2 Nos of 6mm dia M.S.rod at every three alternate layers and the cost shall inclusive of iron reinforcement, Brick work etc, complete as per standard specification - Ground Floor			m2	

Sl No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
15	54.80	M3	Plain Cement Concrete 1:1.5:3 (one cement, one and half fine aggregates and three coarse aggregates) using 20mm size ISS HBG metal including cost and conveyance of all materials to site and including for the mixing, laying and labour charges and all incidental charges etc., complete as per standard specification			cum	
16	638.00	Kg	Supply and fixing of M.S Grills with Doors and Windows with one coat of Red oxide with Primer including all costs such as welding, grinding and fabrication charges, cost and conveyance of all materials to site etc. complete as per standard specification.			Kg	
17	500.29	M2	Special ceiling plastering in all floors and finishing the exposed surface of RCC items of work such as slab, beam, sunshade, fascia, canopy slab, staircase waist slab, landing slab etc., with cement mortar 1:3 (One cement and three sand) 10mm thick including hacking the surfaces and providing cement mortar nosing, beading for sunshade, staircase, step, landing slab etc., including neat finishing and curing etc., complete complying with standard specification and as directed by the departmental officers			sqm	
18	33.00	M2	Special Plastering with cement mortar 1:3 mix (One cement and three sand) 20mm thick including cost and conveyance of all materials, finishing, curing and all labour charges etc. complete as per standard specification			sqm	
19	1543.27	M2	Plastering with cement mortar 1:5 (One cement and five sand) 12mm thick in all floors including cost and conveyance of all materials to site etc. complete as per standard specifications			sqm	
20	19.96	M2	Weathering Course with Concrete Broken Brick (S.I.No.278) & (P & D) Data 54. Jelly 20mm gauge in pure slaked lime (no sand to be added) over roof slab, the proportion of brick jelly to lime being '32 to 12.5 well beaten with wooden beaters for giving required slope and thickness 80mm as directed by the departmental officers. etc., complete.			sqm	

Sl No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
21	245.00	M2	Finishing the top of roof with one course of machine pressed tiles of size 200 mm x 200 mm x 20 mm of approved quality in Cement Mortar 1:3 (One Cement add three sand) 12 mm thick mixed with water proofing compound conforming to ISS at 2% by weight of cement used and the joints pointed neatly to full depth of tiles with the same cement mortar mixed with red oxide and water proofing compound including curing etc. complete			sqm	
22	19.41	M2	Supply and fixing of PVC Solid Doors using 19gauge 19mm MS Sq,tubes for styles and frames, 15mm MS Sq,tubes for top, Lock and bottom rails. The Steel Tubes shall be covered with 5mm thick Solid PVC sheets. Shutter using 5mm thick solid PVC sheets for panelling shall rigidly fixed in position including furniture and fittings. The over all size of styles shall be 50mm X 30mm. The over all size of top rail, Lock rail and bottom rail shall be 75mm X 30mm. The over all size of frames shall be 50mm X 45mm with suitable tabate for housing the shutter etc, complete as per standard specification.			sqm	

SI No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
28	12.00	M3	Supplying and fixing of rolling shutters shall be pull and push type (Mannually operated) made of 18G/3" lath sections which consist of five main parts such as curtain, lock plate, guide channels rollers and hood cover. These five main parts are made out of special components detailed below: curtain shall be of 18G/3" lath sections cut to required size and filled with heavy cast iron / MS clips. For 8'0"(2.45m) high rolling shutter lath sections provided shall be not less than 37 numbers. Lock plate shall be 10G MS sheet and attached to the side brackets with 20mm square bar.Side brackets shall be of 10G MS plate and cast iron "U" clamps shall be rivetted to the side brackets. Roller shall be of heavy cast iron pulleys fitted with heavy duty "C" class 40mm steel pipe and high tensile high carbon coil springs. 2 springs shall be supplied. Side brackets shall be of 10G MS plate and cast iron "U" clamps shall be rivetted to the side brackets. Hood cover shall be of 0.8mm CRCA sheet reinforced with 25mmx25mmx3mm MS angle or gate channel. The rolling shutter in addition to the above should have pulling hook and shall be coated on exposed area with heavy coat of red oxide primer etc., complete.			cum	
24	2.92	M2	Supplying & fixing door shutters for Solid Core Flush Shutters with Teak ply on both side with teak wood lipping alround 35mm thick, single leaf confirming to IS:12406/1989 with 35x12mm T.W. Lipping on all edges with necessary adhesives and CP screws complying with standard specifications. The rate is inclusive of threee coats of best quality varnish but excluding cost of furniture fittings, such as 300 mm tower bolt 2nos, 200mm towerbolt 1 No. 300mm Aldrop 1 No. Alu handle ornamental type 2 Nos and 1No. Door stopper etc complete.			sqm	
25	5.40	M2	Supply and fixing of Stainless steel (Salem stainless steel) Door frame (Box section using stainless steel plate of 1.6mm thick) of size 100mm X 60mm with a rebate of 30 / 35mm X 15mm on one side of the frame including supplying and fixing dovetail splayed end stainless steel holdfast etc.complete as per standard specification.			sqm	

SI No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
26	27.60	M2	Supplying and fixing UPVC (Un-Plasticized Polyvinyl Chloride) Windows of casement type (open) from the profile the size of outer frame 60mm x 58mm and shutter profile are reinforcement with GI/1mm 25GSM and 100% corrosion free, the profiles are multi chambered sections with wall thick of 2mm. The EPDM rubber (black colour) covered with over all the edges of frame and shutter the shutter will be provided with spag multi power point locks and also it operates as handle. The corners and joints should be welded and cleaned. Radiations free pin headed plain or brown colour glass 4mm thick should be provided to the shutter and it should not allow leakage of water even at most ranging storms and should have key lockable action, security protective hinges, strong locking systems and as per size for arresting noise and energy loss. The connecting mechanism between sash and outer frame that enables opening of the window. The window should be fixed to the wall with 100% packing with screws and silicon packing all round the frames. The window should be got approved from the executive Engineer before use on work			sqm	
27	25.00	M2	Manufacturing, Supplying and Fixing of Stainless Steel Hand rails for staircase using 50mm dia 304L Grade Stainless Steel pipe of 1.60mm thick at required locations to a height of 900mm from finished floor level welded to 38mm dia Stainless Steel pipe post of 1.00mm thick as vertical at 900mm centre with 2 Nos. of 25mm dia intermediate horizontal stainless steel pipe of 1.60mm thick in between. The vertical pipe has to be welded to the 100 X 100 X 6mm MS base plate encased in the base concrete. The rate is inclusive of the charges for cutting, bending, welding, grinding, polishing, conveyance, electrical charges, etc. complete			sqm	

SI No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
28	1942.64	Rm	Painting two coats of newly plastered wall surface with approved cement paint over cement plastered wall surface, ceiling and including preparing the surface, clean removal of dirt and including necessary plaster of paris putty wherever required and cost of painting materials, brushes, preparation of surfaces and scaffolding charges etc., complete complying with standard specification and as directed by the departmental officer			Rm	
29	68.60	M2	Painting the new iron work with two coats of best approved first quality and colour of synthetic enamel paint over the existing red oxide priming coat in all floors excluding cost of priming coat and including cost of painting materials, brushes, putty, preparation of surfaces and scaffolding charges etc., complete complying with standard specification and as directed by the departmental officer.			sqm	
30	198.00	M2	Paving the floor with design Rajasthan kotta tiles (colour and shade as directed) of size 610 mm x 610mm x 20mm in all floors over a base layer of cement mortar 1:3 (one cement and three sand) 20mm thick laid in-situ and pointed with same coloured cement etc, complete as per standard specification.			sqm	
31	2.00	M3	Plain Cement Concrete 1:8:16 (one cement eight fine aggregates and sixteen coarse aggregates) using 20mm size ISS HBG metal including cost and conveyance of all materials to site and including for the mixing, laying and labour charges and all incidental charges etc., complete as per standard specification			cum	
32	2130.00	Kg	Supplying, fabricating, erecting structural steel work for roofing welded or bolted type using MS channels, angles, plates and round bars etc. conforming to IS specification including primer coating and enamel painting as per Design given by the departmental officers etc, complete as per standard specification			KG	

Sl No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
33	57.82	M2	Fabricating supplying and fixing of pre painted galvanized iron sheets with the following specification. The materials should be of PPGI tile profile with a red colour or any other approved design 0.47 mm thick 24 guage having width 1050 mm. The sheet should be G.I.base pre painted hot dipped galvanized iron sheet and to be fixed with shelf tapping screws,plastic washer.The washer and screws to be fixed by using minute power machine drilled with out damaging the sheets paint coating to be regular modified polyster coat with zinc coating of Z 120 GSM paint thickness the finish should be terra cotta finish like malabar mangalore tiles finish optional matt finish. The sheet to be fixed with making suitable corrugated,cutting the sheet in to the required ssize and making ornamental designs as per the site condition and as directed by the departmental officers.			sqm	
34	1.00	No	Conducting Geophysical survey, quality and quantity test and transportation charges etc, (This includes labour charges in the field, rent of the vehicle for reaching the place, rent of the instrument and <u>excluding charges for the geologist</u>)			1No	
35	5.00	Cum	Random rubble masonry in cement motor 1:5 (one Part of cement, Five part of Sand) mix using all granite stones and bond stones for			Cum	
36	20.56	M2	Paving the floor with design Rectified Glazed ceramic tiles (colour and shade as directed) of size 305 mm x 305mm x 6 mm in all floors over a			sqm	
37	131.92	M2	Dadoing walls with Glazed tiles of sizes 305mm X200mm X 6mm size of approved make and quality and colour Set in cement mortar 1:2			sqm	
38	2.00	No	Supplying and fixing in position C.I.Manhole covers (light or heavy duty) of 600 X 600mm in size of best approved quality and as per			Each	
39	12.00	Rm	Supplying and fixing P.V.C. ventilating shaft of 100mm dia and 3m height of best approved quality and as per standard specifications.			Rm	
40	25.00	Rm	Providing & fixing PVC RAIN WATER DOWNFALL PIPE of 110mm dia with necessary T.W.Clamps Plugs, Shoes,Bemds, other clamps, screws			Rm	
41	3.00	No	Supplying and fixing in position best quality approved make white glazed earthenware wash hand basin of size 550 X 400 mm with a pair			Each	
42	3.00	No	Supplying and fixing in position White Glazed European Water Closet of best quality and approved make with 100mm 'P' os 'S' trap with Double			Each	

Sl No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
43	0.00	0.00	Supplying laying and jointing P.V.C pipes (6Kg/SqCm) of approved quality and best variety conforming to I.S.S & with I.S.I mark, of the 25MM dia,PVC pipe			0	
0	60.00	Rm				RM	
0	60.00	Rm	20mm dia.PVC pipe			RM	
44	3.00	No	Supplying and fixing in position indian make bewelled edge mirror of approved quality and brand of size 600 X 450mm wth necessary plastic			Each	
45	4.00	No	Supplying and fixing best approved quality Brass C.P anodised Towel rail 600mm. long and 20mm Diameter with brackets of same material			Each	
46	6.00	No	Supplying and fixing best approved quality C.P.Soop Tray of size 150mm X 100mm including cost of Teak Woodplugs, brass screws			Each	
47	9.00	No	Supply and fixing of PVC. Nahini / Floor Trap with stainless Steel Gratings - 100 mm x 75 mm including all charges etc, complete as			Each	
48	60.00	No	Supplying laying and jointing G.I. Pipes of approved quality and best variety of B Class pipe of 25mm dia size including fixing G.I specials but			Each	
49	5.00	No	Supplying and fixing in position first quality and approved variety of Gun Metal Gate Valve (Heavy type) with I.S.I.mark of 25mm dia size			Each	
50	2.00	No	Suppling and fixing in position 15mm.diameter brass screw down tap (heavy duty) of approved make conforming to I.S.specifications and quality including cost of shellac , thread etc.complying with standard specifications and including cutting and threading wherever necessary.			Each	
51	0.00	0.00	Supply and fixing of following Plumbing G.I.materials			0	
0	3.00	No	15mm dia G.I Tee			Each	
0	3.00	Rm	15mm dia G.I Elbow			RM	
0	3.00	No	20mm dia G.I coupling			Each	
0	3.00	No	20mm dia G.I Tee			Each	

SI No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
0	3.00	No	20mm dia G.I Elbow			Each	
0	3.00	No	20mm dia G.I Bend			Each	
0	1.00	No	20mm dia G.I union			Each	
0	3.00	No	25mm dia G.I coupling			Each	
0	3.00	No	25mm dia G.I Tee			Each	
0	3.00	No	25mm dia G.I Elbow			Each	
0	3.00	No	25mm dia G.I Bend			Each	
0	1.00	No	25mm dia G.I union			Each	
0	3.00	No	20mm X 15mm dia G.I Reducer			Each	
0	3.00	No	20mm X 15mm dia G.I Reducer Elbow			Each	
0	3.00	No	25mm X 20mm dia G.I Reducer			Each	
0	3.00	No	20mm X 15mm dia G.I Reducer Tee			Each	
0	10.00	Rm	50mm GI pipe			1Rm	
0	5.00	No	50mm GI Elbow			1No	
0	5.00	No	50mm GI tee			1No	
0	5.00	No	50mm GI Coupling			1No	
0	5.00	No	50mm GI Union			1No	
0	5.00	No	50mm GI bend			1No	
0	5.00	No	20mm GI Elbow			No	
0	5.00	No	20mm GI union			No	
0	5.00	No	20mm GM Value			No	
0	5.00	No	20mm GI Bend			No	
0	5.00	No	20mm GI Coupling			No	
0	5.00	No	20mm GI Hex nipple			No	
0	10.00	Rm	20mm GI pipe			Rm	
0	5.00	No	20mm GI Tee			No	

SI No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
52	0.00	0.00	Supplying and fixing in position P.V.C. specials such as plain bend, door bend, plain tee, door tee, offsets,Y-junction, plain or with door of various sizes best quality confirming to I.S.S and providing leakproof joints including fixing to wall and giving connection to the P.V.C, soil stacks, dismantling the brick masonry or R.C.C. floor or Roof slab and redoing the dismantled portion to original condition etc., complete complying with standard specifications.			0	
0	2.00	No	110mm dia PVC Elbow			Each	
0	2.00	No	110mm dia PVC Tee			Each	
0	2.00	No	110mm dia PVC Door Elbow			Each	
0	2.00	No	110mm dia PVC Door Tee			Each	
0	2.00	No	110mm dia PVC Door Yee			Each	
0	2.00	No	90mm dia PVC Elbow			Each	
0	2.00	No	90mm dia PVC Tee			Each	
0	2.00	No	90mm dia PVC Door Elbow			Each	
0	2.00	No	90mm dia PVC Door Tee			Each	
0	2.00	No	90mm dia PVC Door Yee			Each	
53	0.00	0.00	Supplying and fixing in position best quality P.V.C soil/ waste pipes (6KSC) of various sizes having ISI mark and providing leakproof joints including fixing to the wall with P.V.C/ M.S clamps etc., and making connection to all sanitary fittings, dismantling masonry/R.C.C. works wherever necessary and making good the dismantled portion to the original condition, complying with standard specifications.			0	
a	40.00	Rm	110mm dia PVC 6KSC Pipe			Rm	
b	40.00	Rm	90mm dia PVC 6KSC Pipe			Rm	

SI No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
54	1.00	No	Supply and delivery of wet type submersible pumpsetrequired is 75 LPM discharge and 200m Head with stainless steel shaft, bronze impellers, bronze diffusers, C1 casing etc., complete as per relevent ISI specification in 150mm dia borewell. The pump set should be dynamically balanced and should be supplied with ISI marking. The pumpset should be supplied with 5 meter of 3 core copper cable with cable jointing kit free of cost. As per specifications as per IS rules and confirming to ISI standard should also be supplied.(7.50 HP Motor)			1No	
55	1.00	No	Supply and delivery of 7.50HP Three phase 415Volt DOC Panal board with ISI Specification including all charge etc as per standard specification			1No	
56	225.00	Rm	Supply and delivery of 3 core copper flat 4sqm cable as per IS 694 : 1990 . Including packing, loading, frieght, unloading & Stocking, transit insuraance., third party inspection charges etc.			1Rm	
57	200.00	Rm	Supply and erection of 2" UPVC Heavey Pressure Coloum repipe to relvent IS specification including cost of pipe etc complete as directed by the departmental officers			1Rm	
58	2.00	No	Supply and delivery and fixing of HDPE tank Capacity 3000 litres as per IS 12701 / 1996 including loading, unloading, transportation and labour charges for fixing of the GI pipes and specials for pipe connection works including cutting, threading and fixing charges etc., as per standard specification.			1No	
59	2.00	Each	Supply and fixing of 1000 lit HDPE Tank ISI make with all accessories such as Tank Nipple, Washer etc,inclusing cost and conveyance of all materials to site etc, complete as per standard specifications.			Each	

SI No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
60	3.00	No	Supply and fixing of (TNEB) meter Board suitable for 32A Three Phase service connection with 3 Nos. 32A fuse unit (500V) 32A netrual link and earth link (1" x 1/8" Copper flat) on TW plank of size 600mm x 450mm x 19mm with supporting TW reepers of 1"thick an either side with painting with suitable bold and nuts for fixing the TW plank on wall with earth connection and inter connection with 7/20 PVC suited copper wire from EB meter to fuse unit. (SD - 127)			No	
61	3.00	No	Supply and fixing of 32A TPN metal clad switch on suitable angle iron frame work with MS cable entry boxes with PWD earthing.(SD - 157)			No	
62	18.00	Rm	Supply and run of 4 of 4 sq.mm (56/0.3) PVC insulated SC unsheathed Cu.Conductor of 1100V on 7/20 GI bearer wire for service connection mains.(SD - 65)			Rm	
63	3.00	Rm	Supply and run of 2 of 4 sq.mm (56/0.3) PVC insulated Cu Conductor of 1100V grade in 25mm dia GI pipe (Class'B') bent at both ends with necessary angle iron up right and end supports.(SD - 68)			Rm	
64	50.00	Rm	Supply and laying of 3.5 X 35 Sq.mm PVC armoured LTUG cable in a trench to be excavated at a depth of 0.75 metre putting 0.15 mt. Layer of sand and covering the cable completely with bricks and sand and <u>refilling the earth to make good.</u>			RM	
65	40.00	Pt	Wiring with 2 x 1.5 sqmm (22 /0.3) PVC insulated single core unsheathed copper conductor cable of 1100V grade in suitable PVC rigid pipe concealed in wall and ceiling with PVC accessories inflush with wall with 3mm thick hylum sheet cover with TW switch box and 5A F.T. switch with continuous earth wire connection of 14 SWG TC wire for making good of the concealed portion with suitable colour for PVC concealed light point / Fan point (For Electronic regulator). SD 23			Point	

SI No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
66	7.00	Pt	Wiring with 2 x 1.5 sqmm (22 /0.3) PVC insulated single core unsheathed copper conductor cable of 1100V grade in suitable PVC rigid pipe concealed in wall and ceiling with PVC accessories inflush with wall with 150 x 100 x 113 mm TW switch box with 3mm hylum sheet cover for 5A 3 pin non inter locking CS plug with continuous earth wire connection of 14 SWG TC wire and making good of the concealed portion with suitable colour for concealed PVC plug point. SD 38			Point	
67	150.00	Rm	Supply and run of 2 of 1.5 sqmm (22/0.3) PVC insulated SC unsheathed Cu.Conductor of 1100V grade in suitable PVC rigid pipe concealed in wall and ceiling with continuous earth wire connection of 14 SWG TC wire and making good of the concealed portion with suitable colour. SD 54			Rm	
68	25.00	No	Supply and fixing of 30W LED fitting LIGHT EMITTING DIODE etc, complete as per standard specifications Page No.13			Each	
69	2.00	No	Earthing as per P.W.D. standard with an earth electrode of 2Mtr. Class 'B' GI pipe of dia not less than 32mm complete with necessary masonry work.SD 234			Each	
70	1.00	No	Supply and fixing of 3 phase 4 wire 4 way ICDB of 32 A per way with 100 A TPN MC switch with suitable trunking box Ms cable entry boxes and internal connection on suitable angle iron frame work with earth connection SD. 175			Each	
71	2.00	No	Supply and fixing of Horizontal type 4 way triple pole neutral MCB distribution board in sheet steel enclosure with 40 A 4 pole MCB isolater as incoming and 12 Nos. 6A to 32 A SP MCB as outgoing in flush with wall and making good of the concealed portion with earth connection. The MCBDB and MCB's should be with the ISI mark (lik standard make) SD. 179			Each	
72	30.00	Rm	Supply and run of 2 of No.8 SWG GI wire for guarding with cradle with No.8 SWG GI wire at the equal interval of 1.5m SD.75			Rm	

Sl No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
73	30.00	Rm	Supply and run of 4 X 6 sq.mm (84/0.3) 7/20sqmm PVC unsheathed copper cable in suitable PVC rigid pipe concealed on wall and ceiling with continuous earth wire connection of 14 SWG TC wire with painting of suitable colour SD 68			Rm	
74	4.00	No	Supply and fixing of 300mm (12") sweep AC exhaust fan complete with necessary wall opening and making good of the wall. SD 115			Each	
75	5.00	Pt	Wiring with 2 x 4sqmm (56 /0.3) PVC insulated single core unsheathed copper conductor cable of 1100V grade in suitable PVC rigid pipe concealed in wall and ceiling with PVC accessories in flush with wall with 150 x 100 x 113 mm TW switch box with 3mm hylum sheet cover for 15A 3 pin non inter locking CS plug with continuous earth wire connection of 14 SWG TC wire and making good of the concealed portion with suitable colour for concealed PVC power plug point.SD 40			Point	
76	60.00	Rm	Supplying and laying of PVC insulated, PVC sheathed, armoured, LTUG cable of size 2 core 10 sqmm Al.cable clamped on walls etc, complete as per standard specification (SD 198)			Rm	
77	2.00	No	Supplying and fixing of cable gland and termination with earth connection of size 2 core 10 sqmm etc, complete as per standard specification. (SD 182)			Each	
78	1.00	No	Supply and fixing of TNEB Board suitable for 3 Phases 63A service connection made up of suitable angle iron frame work of size 2 feet x 1 1/2 feet using angle iron of size 1 1/2" x 1 1/2" x 1/4" rigidly fixed on wall covered with hylum sheet of size 2 feet x 1/2 feet of 6mm thickness with necessary bolts and nuts supports and supply and fixing of 3 Nos 63A fuse units(500V) 1 No. Neutral link, copper earth flat of size 1" x 1/4" with inter connection of EB meter to fuse units by 7/16 PVC insulated copper wire with earth connection complete.SD 129			Each	
79	1.00	No	Supply and fixing of 32 A TPN MC switch on incoming and 3 Nos 32 A DPMC Switch (Front Handle) as outgoing with suitable adaptor box with suitable MS cable entry box trunking boxes and internal connections on internal connections on suitable AI frame work with earth connection etc. complete.SD 172			Each	

SI No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
80	1.00	No	Supply and fixing of 3 phase 4 wire 4 way ICDB of 16 A per way with 32 A TPN MC switch with suitable MS cable entry boxes trunking box and internal connections on suitable angle iron frame work with PWD earthing etc. complete. SD 173			Each	
81	1.00	No	Earthing as per the ISI specification with an earth electrode of 2.1mt class 'B' GI pipe of dia not less than 40mm, with copper earth plate of size 125mm x 50mm x 6mm, with necessary funneling arrangements with necessary masonry work and with 38mm RCC cover slab for the brick masonry. SD 233			Each	
82	51.00	Rm	Supply and run of 2 of 4sqmm (56/0.3) PVC insulated SC unsheathed Cu.Conductor of 1100V Grade in suitable PVC rigid pipe concealed in wall and ceiling with continuous earth wire connection of 14SWG Cu wire and making good of the concealed portion with suitable colour (SD57)			Rm	
83	34.00	Rm	Supplying and Laying of 3½ x 50 sq.mm PVC armoured LTUG cable in a trench to be excavated at a depth of 0.75 M putting 0.15 M layer of sand and covering the cable completely with bricks and sand and refilling the earth to make good. [SD 206]			RM	
84	15.00	Rm	Supplying of 4 x 10 sq.mm PVC armoured LTUG cable in a trench to be excavated at a depth of 0.75 M putting 0.15 M layer of sand and covering the cable completely with bricks and sand and refilling the earth to make good. [SD 202]			RM	
85	1.00	No	Supplying and fixing of 1200mm (48") sweep AC ceiling fan complete with regulator with 1M down rod including S & F of fan clamp with side plates and cross arm SD 107			Each	
86	1.00	No	Brick Lining for 300mm thick in furnace roof Fibre Li 2800L X 900W X 700H in mmning chamber size, Door operation : Up & Down movement manual operated max operating temperature : 700- 900 Dec Celsius. Etc. complete.			Each	

SI No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
87	1.00	set	LPG Burner set with LPG Bank & Control Panel: Supply of 4 Nos, 5 Burner with Blower and Fully auto control system like 0,000 Kcal Capacity LPG Fired Ignition, Flame sensor and Auto cut off incorporated in a separate sequence controller equivalent to Imported Control system for air and LPG with auto Igniting system and supply of 20 + 20 cylinder bank with pipeline from LPG cylinder bank up to each Burner end by using TATA "C" class grade material pipe with required material etc. complete			Each	
88	1.00	No	3 hp motor 2no. for use to Id fan & 1hp motor use for wet scrubber Wet Scrubber for gas cleaning system: The system should be enhanced with Stainless steel cylinder and SS ID fan (3hp motor x 2nos. With ISI standard) to avoid rusting, Volume of water should be increased for effective scrubbing.			Each	
89	1.00	No	Guy Supported Chimney: This is a Cylindrical type MS IS - 2062 quality, 8MM Plate Chimney With two coated of aluminium Heat Resistance Paint Externally, 7000 mm, Long Bottom Cylindrical Chimney. It is Rested on 16mm type MS IS - 2062 Quality (100 feet Thick Base Flange and Stool Flange 16mm Thick with 12mm Gusset Support, Cylindrical Chimney Mounted on foundation 12nos x 25mm Dia Bolt, Nut Joints, Top 1 Cylindrical Shell Boiler Quality 8mm Plate x 7000mm long base chimney. It is Rested 50mm width base Flange & wind force curtain MS Flat Set, with Lightning arrestor 25mm x 3mm copper flat earthing, with easy hinges type manual opened manhole door, necessary for pollution control board monitoring sample ports arrangement ladder assembly with safety guard set 70 feet full height, one sets of detachable platform, over all size: 800mm Dia x 400mm Dia x 21000mm length with necessary all arrangements etc., complete			Each	
90	1.00	No	Erection, Testing and Commissioning charges for Gasifier etc, complete			Each	

SI No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
91	0.00	0.00	Supplying laying and jointing P.V.C pipes (6Kg/SqCm) of approved quality and best variety conforming to I.S.S & with I.S.I mark, of the following sizes including cutting , Fixing to PVC specials using Adhesive but excluding cost of such specials and fixing to wall with necessary teak - Wood Plugs,PVC Clamps and screws,making holes on the wall or drilling holes in roof and making good the dismantled portions to original condition with necessary brick work and plastering wherever necessary with necessary scaffolding charges.			0	
0	130.00	Rm	25MM dia,PVC pipe			RM	
0	130.00	Rm	20mm dia.PVC pipe			RM	
92	90.00	Rm	Supplying laying and jointing G.I. Pipes of approved quality and best variety of B Class pipe of 25mm dia size including fixing G.I specials but excluding cost of such specials cutting threading of pipes and fixing to wall with necessary teak wood plugs, clamps and screws masking holes on the wall or drilling holes in roof and making good the dismantled portions to original conditions with necessary brick work and concrete and plastering where ever necessary with necessary scaffolding charges. The pipes are to be painted with two coats of good variety and best approved quality of synthetic enamel paint over a priming coat of red-oxide primer etc. complete			RM	
93	4.00	No	Supplying and fixing in position first quality and approved variety of Gun Metal Gate Valve (Heavy type) with I.S.I.mark of 25mm dia size including cost of Shellac , thread etc.,including labour for cutting and threading of G.I.Pipes etc.,complete complying with standard specifications for both internal and external water Supply arrangements.			Each	
94	7.00	No	Suppling and fixing in position 15mm.diameter brass screw down tap (heavy duty) of approved make conforming to I.S.specifications and quality including cost of shellac , thread etc.complying with standard specifications and including cutting and threading wherever necessary.			Each	

Sl No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
95	36.25	M3	Providing and laying, spreading and compacting graded stone aggregate to wet mix macadam (WMM) specification including premixing the material with water at OMC in mechanical mix plant carriage to mixed material by tipper to site laying in uniform layers with paver in sub base / base course on well prepared surface and compacting with vibratory roller to achieve the desired density complete as per clause 406 of MORTH specifications.			cum	
96	298.05	M2	Supplying and laying Rubberised interlocking Paver block M40 grade Providing and laying of 83mm thick high strength type conforming IS 15658-2006 of rubberized interlocking paver block in size of minimum compressive strength of 40 N/mm2 in uniform shape of approved make to be laid in flurring bone pattern with stone dust cushion below the uniform shape of approved non skitting surface in the top and the rate including levelling the base preparation of pavers as sub base, Stone Dust cushion 150mm thick laying out of pavement cut the pieces to fix the edge vibrating the pavers, sweeping transporting loading unloading of laying paver block as per standard specification,.			sqm	
97	100.00	No	Drilling of 150mm dia vertical bores in hard rock formation to any required depth as directed by the departmental officers including labour charges for inserting casing pipe, assembling in the drilled hole, including welding the joints if necessary grouting the casing pipe etc, and including transportation charges for the rig and supporting vehicles from one place to another place.			1Rm	
i	150.00	m	0-150 m			1 Rm	
ii	30.00	m	151-180			1 Rm	
iii	20.00	m	181-200			1 Rm	
98	6.00	No	Supply and delivery of unplasticised ribbed screen PVC casing pipe of the 140mm dia in 3m length with screwed and socket end and centering guide for every 15m length of pipes as per IS / 12818 / 92 and as amended from time to time to suit the borewell upto 80m depth (C.S) with ISI marking including, loading, unloading , freight, stacking and transit insurance charges etc. complete.			1Rm	

SI No	Qty		Description of work	Rates in		Per	Amount
				Figures	Words		
99	4.00	M2	Supplying and fixing UPVC (Un-Plasticized PolyvinylChloride) Louvered Ventilators of from the profile the size of outer frame 60mm x 58mm and shutter profile size of 60 x 78mm both profiles are reinforced with GI/1mm 125GSM and 100% corrosion free, the profile are multi chambered sections with wall thick of 2mm. The EPDM rubber (black colour) covered with all over the edges of frame and shutter. The corners and joints should be welded and cleaned. Radiations pin headed glass 4mm thick should be provided in the louvers. The window should be fixed to the wall with 100% packing with screws and silicon packing all round the frames. The ventilator should be got approved from the Executive Engineer before use on work			sqm	