

MYLAUDY TOWN PANCHAYAT
KANNIYAKUMARI DISTRICT - KANNIYAKUMARI ZONE

_ TENDER SCHEDULE _

Name of Work : Supply and delivery of three wheeler Sealed Lead Acid Battery Operated Vehicle (4 Nos) for Mylaudy Town Panchayat.

Scheme Name : KNMT 21 - 22

Estimate amount : ` 6,20,000/-

Tender Date :

Schedule issued to M/s:

Closing Time :

Schedule cost `:

Opening Time :

Remitted vide chellan No:

EMD Rupees (`) :

Date:

**THE EXECUTIVE OFFICER
MYLAUDY TOWN PANCHAYAT**

Sl. No.	Qty	Description of work		Unit	TNDSS & MORTH No.	Rate in	
						Figures	Words
01.		Supply and delivery of three wheeler Sealed Lead Acid Battery Operated Vehicle with following Specifications					
		Sl.No	Parameters	Specification			
		1.	Battery operated Vehicles having 3 wheels Design	Vehicles having 3 construction for and carrying of collected Municipal Solid Waste wheels. Robust in			
		2.	Chassis Construction	Ladder type welded construction consisting of two symmetrical beams / rails / channels running the length of the cart with transverse cross - members connecting them fabricated using CRC MS square pipes of suitable size with Anti Rust Proof powder coating			
		3.	Dimensions of cart	Overall Length: 2760 mm + 5KNMT Tolerance Overall width1000 mm 5KNMT Tolerance			

Sl. No.	Qty	Description of work		Unit	TNDSS & MORTH No.	Rate in	
						Figures	Words
		4.	Motor	Brushless DC Motor 1500W / 60V Original			
		5.	Transmission	Single central axis differential drive with Both forward and reverse direction			
		6.	Ground Clearance	160 mm To 170 mm .			
		7.	Pay Load	Not less than 375 Kgs			
		8.	Range per Charge	80 -100 Km per Charge			
		9.	Speed of Vehicle	Maximum 25 Kms per Hour			
		10.	Rear Cargo Box Size (LxBxH)	a) Dimension: Not less than 1400 mm x 1000 mm x 450 mm (LxBxH). b) Should be fabricated using MS Sheet, MS Square pipes of suitable thickness and size). c) Rear Door: Foldable single door arrangement. d) Side door foldable single door arrangement. e) Both side doors should be made of MS Sheet of thickness not less than 0.6 mm f) Flooring should be made of MS Sheet of thickness not less than 1.6 mm			
		11.	Grade ability {Climbing ability}	7 degree (Minimum).			
		12.	Brake System	Double Rear drum Pedal Type			
		13.	Wheels & Tyres	Front: 3.75 - 12 (6PR) - 1 No. Rear: 3.75 – 12 (6PR) - 2 Nos. Spare tyre assy. - 1 No.			
		14.	Seating Capacity	Cushioned seat to accommodate 2 Person			
		15.	Cabin	Weather proof complete metal enclosed cabin with Windscreen glass (Toughened) for driver protection with necessary frame structure for protection from heat and rain			
		16.	Suspension	Front: Heavy duty Hydraulic shocker. Rear: Leaf spring with hydraulic shocker			
		17.	Charger	15 Amp SMPS Charger			

Signature of contractor & address

Sl. No.	Qty	Description of work		Unit	TNDSS & MORTH No.	Rate in	
						Figures	Words
		18.	Accessories:	Accessories: 1) Head lamp, Speedo Meter, front & rear indicators should be provided. 2) Fire Extinguishers. 3) Functional safety by providing circuit breaker (MCB) 4) Public Addressing System 5) GPS tracking			
		19.	Battery Capacity	100 AH - 48 V. SEALED LEAD ACID ION battery			
		20.	Charging Duration	Not more than 3 Hours			
		21.	warranty for vehicles	The successful bidder should provide one year warranty for vehicles including repair and replacement			
		22.	Warranty for Sealed Lead Acid Battery	The successful bidder should provide three years warranty for Sealed Lead Acid Battery			
		**For the first one year the operation and Maintenance cost per BOV shall be the responsibility of the supplier.					
	4 Nos.	Three wheeler Sealed Lead Acid Battery Operated Vehicle		1No. (one number)			

(Approved in Item No. 01 to 01 only)

Signature of contractor & address