Item Rate BoQ

Tender Inviting Authority: Executive Officer Town Panchayat Manimuthar

Help

Name of Work: Purchase of 5 Nos of Battery Operated vehicles (Three Wheeler) with Lithium Ion battery for conservancy purpose in Manimuthar Town Panchayat

Contract No: 198/2022/Package 1

ı	Name of the
	Bidder/ Bidding
	Firm /
	Company :

PRICE SCHEDULE

(This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevent columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only)

anowed to their the blader Name and Values only)									
NUMBER#	TEXT #	NUMBER#	TEXT #	NUMBER	NUMBER#	NUMBER #	TEXT #		
SI. No.	Item Description	Quantity	Units	Estimated Rate in Rs. P	BASIC RATE In Figures To be entered by the Bidder	TOTAL AMOUNT Without Taxes in Rs. P	TOTAL AMOUNT In Words		
1	1) Vehicles having 3 should be Robust in construction for and carrying of collected Municipal Solid Waste.Wheels .2) Ladder type welded construction consisting of two symmetrical beams/ rails/ channels running the length of the cart with transverse cross - members connecting them fabricated using CRC MS square pipes of suitable size with Anti Rust Proof powder coating 3)Overall Length: 2760mm + 5% Tolerance Overall width 1000mm 5% Tolerance, 4)Brushless DC Motor 1500W/60V Original 5) Single central axis differential drive with Both forward and reverse direction 6)160 mm To 170mm 7)Not less than 375 Kgs 8)80 -100 Km per Charge 9) Maximum 25 Kms per Hour 10)a).Dimension: Not less than1400mm x 1000mm x 450mm (L X BX H) 10b) Should be fabricated using MS Sheet, MS Square pipes of suitable thickness and sizes.(Rear Door: Foldable single door arrangement) Side door foldable single door arrangement 10 e) Both side doors should be made of M.S Sheet of thickness not less than 0.6 mm 10f) Flooring should be made of M.S Sheet of thickness not less than 0.6 mm 10f) Flooring should be made of M.S Sheet of thickness not less than 0.6 mm 10f) Flooring should be made of M.S Sheet of thickness not less than 0.6 mm 10f) Flooring should be made of M.S Sheet of thickness not less than 0.6 mm 10f) Flooring should be made of M.S Sheet of thickness not less than 0.6 mm 10f) Houther of thickness not less than 1.6 mm, 11) 7 degree (Minimum) 12)Double Rear drum Pedal Type 13)Front: 3. 75 - 12 (6PR) - 1 No. Rear: 3. 75 - 12 (6PR) - 2 Nos. Spare tyre assy 1 No 14)Cushioned seat to accommodate 2 Person 15) Weather proof complete metal enclosed cabin with Windscreen glass (Toughened) for driver protection with necessary frame structure for protection from heat and rain 16)Front: Heavy duty Hydraulic shocker. Rear: Leaf spring with hydraulic shocker, 17) 15 Amp SMPSCharger 18)Accessories: 1). Head lamp, Speedo Meter, front & rear indicators should be provided.2) Fire Extinguishers. 3) Functional safety by providing circuit breaker (MCB)	5.00	Nos			0.00	INR Zero Only		

Total in Figures		0.00	INR Zero Only
Quoted Rate in Words	INR 2	Zero Only	